



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

## TECHNICAL DATA SHEET

### SILICONE SPRAY

<b>Article number:</b>	<b>27008</b>
<b>Intended use:</b>	Car refinishing Product/ Lubricant
<b>General characteristics:</b>	High quality silicone spray to lubricate and protect plastic or rubber parts.
<b>Product characteristics:</b>	<ul style="list-style-type: none"><li>▪ Excellent adhesion</li><li>▪ Water-repellent</li><li>▪ Prevents freezing and drying out of rubber parts</li><li>▪ Prevents creaking and squeaking of plastic parts</li><li>▪ Outstanding mechanical and thermal stability</li><li>▪ Resistant to weather influences</li><li>▪ Resistant to weak acids and bases</li><li>▪ Directed jetspray</li></ul>

### Applications:

Door rubbers	Creaking plastic parts
Dashboards	Bumpers
Sunshine roofs	Rails (caravan, blinds)
Sliding doors	Saw blades
Remove agents for moulds	

### Physical and Chemical Characteristics:

Contents	: 400 ml
Basis	: Polydimethylsiloxaan
VOC-content	: Approximately 88% w/w
Colour	: Transparent
Scent	: Characteristic
Relative density at 20°C	: 0,72 g/ml
Vapour pressure at 20°C	: 3 to 4 bar
Refractive Index at 25°C	: 1,403
Disruptive strength	: 14 kv/mm at a temperature of 20°C
Resistance	: 4 x 10 <sup>15</sup> Ohm/cm
Temperature resistant	: -50°C to +200°C
pH-value	: Neutral



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

## Usage:

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

Apply silicone spray in a thin layer. Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).

*Data: 05, October 2014*

*This release replaces all eventually earlier issued versions.*

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)*

*See information on safety in Safety Data Sheet.*